Flap Gate Valve

The AWMA Flap Gate is a one way/non-return flap gate valve designed to prevent backflow.



Features

- Effective backflow prevention device.
- Top hinged one way flap valve.
- Double pivot hinges as standard.
- Gravity and head pressure achieve automatic sealing.
- · Low head loss.
- Full perimeter sealing.
- Suitable for up to 10m head pressure.
- Custom designed and fabricated to suit any size or shaped orifice.
- · Requires minimal civil works to install.

Applications

- The Flap Gate range is used for many applications across all industry sectors.
- Commonly used for tidal and flood mitigation as well as sewage and stormwater management.

Sizes

- All AWMA water control gates are custom sized to ensure they meet specific site and operational requirements.
- Customisation reduces installation and civil costs.

Materials

- · Constructed from marine grade aluminium or grade 316L stainless steel.
- Materials used in the construction of the Flap Gate range have a high corrosion resistance and can be operated for many years with minimal maintenance.

Sealing

 The sealing ability of this gate exceeds that required by the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.

Quality

- All fabrication is in accordance with the 'Australian Technical Specification for Fabricated Water Control Infrastructure', AS/NZS 1554.6 and AS/NZS 1665.
- All stainless steel welding is continuous to avoid crevice corrosion.
- All procedures are in accordance with AWMA's accredited ISO 9001 Quality Management System to ensure each gate is manufactured to a high standard, tested and ready for trouble free operation post approved installation.

Operation

- Gravity and head pressure automatically operate gate for one-way flow only.
- Lifting lugs or cable winch optional to raise the gate in emergency situations.

Maintenance

- The Flap Gate range has a minimum 25year design life.
- Minimal maintenance is required offering low "whole of life" costs.
- If required, all the wearing components can be changed with ease, on site.

Mountina

- Flap Gates are typically wall mounted.
- Spigot or pipe mount options available.







Phone +61 3 5456 3331 Email info@awma.au.com 118 Roviras Road, PO Box 433, Cohuna Victoria 3568