

DLF PENSTOCKS

AWMA's DLF Penstock range consists of downwards opening, decant weirs.

FEATURES

- Accurate overshoot flow and upstream pool level control.
- The unique design keeps spindles out of the open water way to eliminate obstruction and maintenance issues.
- Bi-directional sealing optional.
- Single and dual spindle configurations available.
- Both rising and non-rising spindle configurations available.
- Custom designed and fabricated to suit any size or shaped orifice.

APPLICATIONS

- The DLF Penstock range is utilised for applications across all industry sectors.
- Isolation and flow regulation.
- Small to medium decanting applications.



awma

DLF PENSTOCKS



DESIGN

DESIGN SUPPORT

- AWMA's design team will provide full support to ensure the most appropriate solution is developed and specified during the preliminary design.

SIZES

- All AWMA water control gates are custom sized to ensure they meet specific site and operational requirements.
- Customisation reduces installation costs.

MATERIALS

- AWMA select materials to meet a minimum design life of 25 years. Where required, AWMA can offer higher grade materials, coatings and protection systems to extend the design life to 100+ years.
- AWMA use ultra high molecular weight polyethylene (UHMWPE) for penstock door guides and/or wedges to provide maintenance free bearing surfaces.
- Plasticised PVC or EPDM are used for the manufacture of seals. These materials offer superior endurance in wastewater and freshwater applications.
- * Materials used for penstock door and frames include marine grade aluminium and grades 304, 316, 2205 and 2507 stainless steel.
- Materials used in the construction of the DLF Penstock range have a high corrosion resistance and can be operated for many years with minimal maintenance.

SEALING

- The sealing ability of this gate exceeds that required by the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.

MAINTENANCE

- The DLF Penstock range has a minimum 25 year design life.
- Minimal maintenance is required offering low 'whole of life costs'.
- If required, all the wearing components can be changed, with ease, on site.

MANUFACTURE

QUALITY

- All fabrication is in accordance with the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.
- All stainless steel welding is continuous to avoid crevice corrosion.
- All procedures are in accordance with AWMA's accredited ISO 9001 Quality Management System to ensure each gate is manufactured to a high standard, tested and ready for trouble free operation post approved installation.

INSTALLATION

MOUNTING OPTIONS

- The DLF Penstocks are typically wall mounted.

ACTUATION SYSTEMS

- Choose from
 - Rising Spindle,
 - Non-Rising Spindle or
- Handwheel, electric, hydraulic or pneumatic actuator.
- Portable actuation systems available.

OPERATION SYSTEMS

- Integration into new or existing SCADA systems optional.
- Global, web based operating platforms for remote control and monitoring.

COMMISSIONING

DOCUMENTATION AND TRAINING

- Detailed documentation on operation, testing procedures and maintenance will be provided with all AWMA water control solutions.
- Comprehensive on and/or off site training available.