SEGMENTED STOPBOARDS

AWMA's Segmented Stopboard range consists of fabricated modular segments of any size, joined to effectively isolate flows for regulation, re-direction or containment.

FEATURES & BENEFITS

- Modular segments are fabricated to suit project requirements.
- Designed to suit square and rectangular openings up to 6m wide.
- Allows overshot level regulation as well as flow isolation.
- Consists of dedicated extruded section with embedded seals.
- Uni-directional as standard. Bi-directional sealing designs available upon request.
- Storage solutions available.

APPLICATIONS

- The Segmented Stopboard range is utilised for applications across all industry sectors.
- Isolation of open channel flow for maintenance purposes.
- Isolation and regulation of open channel flow.
- Regulation of environmental flows.



www.awmawatercontrol.com.au



SEGMENTED STOPBOARDS

DESIGN

DESIGN SUPPORT

 AWMA's R&D and Engineering teams are available under Early Contractor Involvement (ECI), to assist in developing water control and screening solutions for bespoke green-field and brown-field sites.

SIZES

- All AWMA water control gates are custom sized to ensure they meet specific site and operational requirements.
- Customisation reduces installation costs.

MATERIALS

- AWMA select materials to meet a minimum design life of 25 years. Where required, AWMA can offer higher grade materials, coatings and protection systems to extend the design life to 100+ years.
- · Mostly constructed from marine grade aluminium.
- Materials used in the construction of the Segmented Stopboard range have a high corrosion resistance and can be operated for many years with minimal maintenance.

SEALING

• The sealing ability of this gate meets the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.

MAINTENANCE

- The Segmented Stopboard range has a minimum 25 year design life.
- Minimal maintenance is required offering low 'whole of life costs'
- If required, all the wearing components can be changed, with ease, on site.

MANUFACTURE

QUALITY

- All AWMA products meet relevant Australian and international standards.
- All fabrication is in accordance with the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.
- AWMA hold international accreditations for ISO 9001; Quality, ISO 14001; Environment and ISO 45001 OH&S management.
- AWMA's Integrated Management System aims to provide a framework to deliver products and services that consistently exceed customer expectations.

INSTALLATION

MOUNTING OPTIONS

- The Stopboard frames are designed for wall, channel or embedded side frame mounting.
- The sill is available for use on either a flat or raised sill.

ACTUATION SYSTEMS

• Mechanical lifting devices available.

OPERATION SYSTEMS

Insertion and removal of boards via the AWMA manual Lifting Ladder.

COMMISSIONING

DOCUMENTATION AND TRAINING

- Detailed documentation on operation, testing procedures and maintenance will be provided with all AWMA water control solutions.
- · Comprehensive on and/or off site training available.



HEAD OFFICE

Phone +61 3 5456 3331 Email info@awmawatercontrol.com.au 118 Roviras Road, PO Box 433, Cohuna Victoria 3568, Australia.

www.awmawatercontrol.com.au

