

TLF PENSTOCKS

AWMA's TLF Penstock range consists of an undershot gate with a full perimeter seal, providing flow isolation for fully submerged on or off seating applications.

FEATURES & BENEFITS

- Resilient seals around all four sides of the aperture.
- Excellent sealing for med-high head applications.
- Can be modulating for regulation of flows.
- Bi-directional sealing optional.
- Both rising and non-rising spindle configurations available.
- Custom designed and fabricated to suit any size or shaped orifice.

APPLICATIONS

- Full perimeter seal provides excellent sealing performance for applications across all industry sectors.
- Isolation of pipe openings and orifices over 300mm in diameter.
- Suitable for flow isolation or regulation.



awma
Water Control Solutions



TLF PENSTOCKS

DESIGN

DESIGN SUPPORT

- AWMA's R&D and Engineering teams are available under Early Contractor Involvement (ECI), to assist in developing water control and screening solutions for bespoke green-field and brown-field sites.

SIZES

- All AWMA water control gates are custom sized to ensure they meet specific site and operational requirements.
- Customisation reduces installation costs.

MATERIALS

- AWMA select materials to meet a minimum design life of 25 years. Where required, AWMA can offer higher grade materials, coatings and protection systems to extend the design life to 100+ years.
- AWMA use ultra high molecular weight polyethylene (UHMWPE) for penstock door guides and/or wedges to provide maintenance free bearing surfaces.
- Plasticised PVC or EPDM are used for the manufacture of seals. These materials offer superior endurance in wastewater and freshwater applications.
- Materials used for penstock door and frames include marine grade aluminium and grades 304, 316, 2205 and 2507 stainless steel.
- Materials used in the construction of the TLF Penstock range have a high corrosion resistance and can be operated for many years with minimal maintenance.

SEALING

- The sealing ability of this gate meets the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.

MAINTENANCE

- The TLF Penstock range has a minimum 25year design life.
- Minimal maintenance is required offering low "whole of life costs".
- If required, all the wearing components can be changed, with ease, on site.

MANUFACTURE

QUALITY

- All AWMA products meet relevant Australian and international standards.
- All fabrication is in accordance with the 'Australian Technical Specification for Fabricated Water Control Infrastructure'.
- All stainless steel welding is continuous to avoid crevice corrosion.
- AWMA hold international accreditations for ISO 9001; Quality, ISO 14001; Environment and ISO 45001 OH&S management.
- AWMA's Integrated Management System aims to provide a framework to deliver products and services that consistently exceed customer expectations.

INSTALLATION

MOUNTING OPTIONS

- Ideal for pit and headwall installations
- The TLF Penstocks are typically wall mounted.

ACTUATION SYSTEMS

- Choose from
 - Rising Spindle,
 - Non-Rising Spindle or
 - AWMA's Rising/Non-Rising Spindle Arrangement

OPERATION SYSTEMS

- Integration into new or existing SCADA systems optional.
- Global, web based operating platforms for remote control and monitoring.

COMMISSIONING

DOCUMENTATION AND TRAINING

- Detailed documentation on operation, testing procedures and maintenance will be provided with all AWMA water control solutions.
- Comprehensive on and/or off site training available.